

**UNCLASSIFIED**

---

**AD 296 208**

*Reproduced  
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY  
ARLINGTON HALL STATION  
ARLINGTON 12, VIRGINIA**



---

**UNCLASSIFIED**

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

63-2-4

NOLTR 61-87

ASTIA  
AS AD NO. 296208

296 208

NOL

25 OCTOBER 1962

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

NOLTR 61-87

ASTIA  
RECEIVED  
FEB 14 1968  
ASTIA

THE DETERMINATION OF CRITICAL  
ROUGHNESS HEIGHT FOR BOUNDARY  
LAYER TRANSITION

- RELEASED TO ASTIA  
BY THE NAVAL ORDNANCE LABORATORY
- ☒ Without restrictions
  - ☐ For Release to Military and Government Agencies Only.
  - ☐ Approval by BuWeps required for release to contractors.
  - ☐ Approval by BuWeps required for all subsequent release.

UNCLASSIFIED  
NOLTR 61-87

Ballistics Research Report 49

THE DETERMINATION OF CRITICAL ROUGHNESS HEIGHT  
FOR BOUNDARY LAYER TRANSITION

Prepared by:

W. C. Lyons, Jr.  
Z. J. Levensteins

ABSTRACT: A method is presented which allows a determination of the critical roughness height required to produce premature boundary layer transition. This method is applicable to cases involving compressibility, heat transfer, and pressure gradient. The results are presented in graphic form which allows a relatively simple application of the method.

PUBLISHED DECEMBER 1962

U. S. NAVAL ORDNANCE LABORATORY  
WHITE OAK, MARYLAND

1  
UNCLASSIFIED

25 October 1962

THE DETERMINATION OF CRITICAL ROUGHNESS HEIGHT FOR  
BOUNDARY LAYER TRANSITION

This work was sponsored by the Re-Entry Body Section of the Special Projects Office, Bureau of Naval Weapons, under task number NOL-363.

The authors wish to acknowledge the work performed by Mr. Hensel S. Brown who prepared the equations for the digital computer and assisted in performing the numerical calculations. Acknowledgement is also made of the work performed by Miss Amy A. Chamberlin who plotted the many curves presented in this report.

R. E. ODENING  
Captain, USN  
Commander

*A. E. Seigel*  
A. E. SEIGEL  
By direction

## CONTENTS

	Page
SYMBOLS.....	vi
INTRODUCTION.....	1
DEVELOPMENT OF METHOD.....	2
CALCULATIONS AND PRESENTATION OF RESULTS.....	4
GENERAL APPLICATION OF METHOD.....	7
APPLICATION OF METHOD TO A CONE.....	9
CONCLUSION.....	10
REFERENCES.....	11

## ILLUSTRATIONS

## Figure

## Title

1

Variation of Roughness Reynolds  
Number with Momentum Thickness  
Reynolds Number

(a) $S_w = 1.0$	$\beta = 2.0$ .....	13
(b) $S_w = 1.0$	$\beta = 1.5$ .....	14
(c) $S_w = 1.0$	$\beta = 1.0$ .....	15
(d) $S_w = 1.0$	$\beta = 0.5$ .....	16
(e) $S_w = 1.0$	$\beta = 0.3$ .....	17
(f) $S_w = 1.0$	$\beta = 0$ .....	18
(g) $S_w = 1.0$	$\beta = -0.1$ .....	19
(h) $S_w = 1.0$	$\beta = -0.1295$ .....	20
(i) $S_w = 1.0$	$\beta = -0.13$ .....	21
(j) $S_w = 0$	$\beta = 2.0$ .....	22
(k) $S_w = 0$	$\beta = 0.5$ .....	23
(l) $S_w = 0$	$\beta = 0$ .....	24
(m) $S_w = 0$	$\beta = -0.14$ .....	25
(n) $S_w = 0$	$\beta = -0.1988$ .....	26

## ILLUSTRATIONS (Cont'd.)

Figure	Title	
1 (Cont'd.)	(o) $S_w = -0.4$	$\beta = 2.0$ ..... 27
	(p) $S_w = -0.4$	$\beta = 0.5$ ..... 28
	(q) $S_w = -0.4$	$\beta = 0$ ..... 29
	(r) $S_w = -0.4$	$\beta = -0.2$ ..... 30
	(s) $S_w = -0.4$	$\beta = -0.24$ ..... 31
	(t) $S_w = -0.8$	$\beta = 2.0$ ..... 32
	(u) $S_w = -0.8$	$\beta = 1.5$ ..... 33
	(v) $S_w = -0.8$	$\beta = 0.5$ ..... 34
	(w) $S_w = -0.8$	$\beta = 0$ ..... 35
	(x) $S_w = -0.8$	$\beta = -0.14$ ..... 36
	(y) $S_w = -0.8$	$\beta = -0.3$ ..... 37
	(z) $S_w = -0.8$	$\beta = -0.325$ ..... 38
	(aa) $S_w = -0.8$	$\beta = -0.3285$ ..... 39
	(bb) $S_w = -1.0$	$\beta = 2.0$ ..... 40
	(cc) $S_w = -1.0$	$\beta = 0.5$ ..... 41
	(dd) $S_w = -1.0$	$\beta = 0$ ..... 42
	(ee) $S_w = -1.0$	$\beta = -0.14$ ..... 43
	(ff) $S_w = -1.0$	$\beta = -0.3$ ..... 44
	(gg) $S_w = -1.0$	$\beta = -0.36$ ..... 45
	(hh) $S_w = -1.0$	$\beta = -0.3884$ ..... 46
2	Variation of Roughness Reynolds Number with Local Temperature .....	47
3	Relation between $\beta$ and $n$ .....	48

ILLUSTRATIONS (Cont'd.)

Figure	Title	
4	Variation of Roughness Reynolds Number with $S_w$ .....	49
5	Variation of Roughness Reynolds Number with $\beta$ ....	49
6	Variation of Roughness Reynolds Number with $M_e$ .....	50



SYMBOLS

$C_F$	mean skin friction coefficient
$k$	height of the roughness element
$M$	Mach number
$n$	correlation number defined by equation (11)
$p$	static pressure
$R$	gas constant in perfect gas law
$Re_\theta$	Reynolds number based on boundary layer momentum thickness and flow conditions which exist just outside of the boundary layer
$Re_k$	Reynolds number based on roughness height and flow conditions which exist just outside of the boundary layer
$R_{kk}$	critical roughness Reynolds number - based on roughness height and flow condition which exist within the boundary layer at a distance $k$ from the wall
$S$	enthalpy function
$T$	absolute temperature
$u$	velocity component tangential to the wall
$x$	coordinate tangential to the wall
$y$	coordinate normal to the wall
$\beta$	pressure gradient parameter
$\gamma$	ratio of specific heats, $\gamma = 1.4$
$\eta$	similarity variable from reference (9)
$\theta$	boundary layer momentum thickness
$\mu$	coefficient of viscosity
$\nu$	kinematic viscosity

SYMBOLS (Cont'd.)

$\rho$	mass density
$\sigma$	Mach number function

Subscripts

e	local flow conditions just outside the boundary layer
k	local flow conditions within the boundary layer at a normal distance k from the wall
o	free stream stagnation value
w	conditions at the wall

## INTRODUCTION

It is often desirable when conducting aerodynamic experiments to insure that the boundary layer flow over the body is turbulent, or to insure that transition from laminar to turbulent flow occurs at a specified point on the body. One method of inducing premature boundary layer transition on a model is by applying roughness to the surface of the body. In this report a method is presented which allows the determination of the minimum height of surface roughness required to produce premature boundary layer transition, provided a certain parameter is assumed as transition criterion. The method may be applied to compressible laminar boundary layer with pressure gradients and heat transfer at the surface.

In the present method it is assumed that a criterion for roughness affected boundary layer transition can be formed by defining a critical roughness Reynolds number,

$$R_{k_k} = \frac{\rho_k u_k k}{\mu_k}, \text{ where } k \text{ is the height of the roughness element}$$

and subscript k indicates the flow properties in the boundary layer a distance k from the surface. Thus, if the parameter  $R_{k_k}$  is smaller than some experimentally determined critical

value, no effect will be made on the boundary layer transition location. Von Doenhoff and Horton (reference (1)) and Smith and Clutter (reference (2)) have satisfactorily correlated subsonic flow transition measurements by utilizing the concept of a critical roughness Reynolds number as defined in this report. In an attempt to correlate results from supersonic boundary layer transition experiments, several different parameters have been proposed by various investigators, references (3), (4), (5), (6), (7), and (8). In the reports by Braslow, Knox, and Horton (reference (7)) and Jackson and Czarnecki (reference (8)), low supersonic boundary layer transition results were correlated by using the critical roughness Reynolds number  $R_{k_k}$ . This correlation

appeared quite satisfactory. Because of simplicity and lack of more reliable supersonic boundary layer transition results, the criterion for roughness induced boundary layer transition has been assumed to be  $R_{k_k}$ , the critical roughness Reynolds number.

In order to know the flow properties within the boundary layer which are necessary to form the critical roughness Reynolds number, the velocity and enthalpy profiles for a compressible laminar boundary layer presented by Cohen and Reshotko in reference (9) have been utilized in the development of the method. The roughness height causing premature transition is then presented in graphical form as  $Re_k$ , a Reynolds number based on roughness height and flow properties which exist just outside of the boundary layer at the location at which transition is to be initiated, versus  $Re_\theta$ , the boundary layer momentum thickness Reynolds number.

#### DEVELOPMENT OF METHOD

Based upon the assumption that the criterion for premature boundary layer transition is the existence of a critical roughness Reynolds number  $R_{kk}$ , the following method for the determination of the critical roughness height can be developed. The critical roughness Reynolds number is defined as:

$$R_{kk} = \frac{\rho_k u_k k}{\mu_k} \quad (1)$$

Using the perfect gas law allows the density to be expressed in terms of the pressure and temperature so that equation (1) may be written as:

$$R_{kk} = \frac{p_k u_k k}{RT_k \mu_k} \quad (2)$$

Upon writing all of the quantities on the right-hand side of equation (2) in ratio form with the exception of the gas constant, R, equation (2) becomes:

$$R_{kk} = Re_\theta \frac{p_k/p_\infty u_k/u_\infty k/\theta}{T_k/T_\infty \mu_k/\mu_\infty} \quad (3)$$

where  $Re_\theta$  is the momentum thickness Reynolds number based on flow properties just outside of the boundary layer.

The assumption that the pressure across the boundary layer is constant makes the pressure ratio,  $p_k/p_e$  in equation (3), unity. Also, by the use of Sutherland's formula, the viscosity ratio can be expressed in terms of the temperatures  $T_k$  and  $T_e$  as:

$$\frac{\mu_k}{\mu_e} = \left( \frac{T_k}{T_e} \right)^{3/2} \frac{1 + 198.6/T_e}{T_k/T_e + 198.6/T_e} \quad (4)$$

The substitution of equation (4) into equation (3) along with the assumption that  $p_k/p_e = 1$ , yields

$$R_{kk} = R_{e\theta} \frac{u_k/u_e \cdot k/\theta \cdot (T_k/T_e + 198.6/T_e)}{(T_k/T_e)^{3/2} (1 + 198.6/T_e)} \quad (5)$$

If the temperature profile expression given in reference (9) is utilized, the temperature ratio can be expressed in terms of the velocity ratio and an enthalpy ratio as:

$$\frac{T_k}{T_e} = \left( 1 + \frac{\gamma-1}{2} M_e^2 \right) \left[ 1 + S_k - \sigma \left( \frac{u_k}{u_e} \right)^2 \right] \quad (6)$$

where:

$$\sigma = \frac{\frac{\gamma-1}{2} M_e^2}{1 + \frac{\gamma-1}{2} M_e^2}$$

Substituting equation (6) into equation (5) and solving for the ratio  $R_{e\theta}/R_{kk}$  gives:

$$\frac{R_{e\theta}}{R_{kk}} = \frac{(1 + 198.6/T_e) \left\{ \left( 1 + \frac{\gamma-1}{2} M_e^2 \right) \left[ 1 + S_k - \sigma \left( \frac{u_k}{u_e} \right)^2 \right] \right\}^{3/2}}{u_k/u_e \left\{ \left( 1 + \frac{\gamma-1}{2} M_e^2 \right) \left[ 1 + S_k - \sigma \left( \frac{u_k}{u_e} \right)^2 \right] + 198.6/T_e \right\} k/\theta} \quad (7)$$

To calculate a value for the ratio  $Re_\theta/R_{kk}$  from equation (7), it is necessary to specify values for  $u_k$ , the velocity, and  $S_k$ , the enthalpy function, at a point in the boundary layer at a distance  $k$  from the wall. This implies that velocity and temperature profiles through the boundary layer must be specified. Cohen and Reshotko (reference (9)) have presented velocity and enthalpy profiles for the laminar compressible boundary layer including the effect of both heat transfer at the wall and a pressure gradient impressed on the boundary layer by the external flow. These velocity and enthalpy profiles are presented as a function of a non-dimensional similarity parameter  $\eta$ .

Since equation (7) involves the parameter  $k/\theta$ , and since it is desirable to express the physical distance from the wall  $k$  in terms of the non-dimensional similarity parameter  $\eta$ , it is desirable to determine the expression for  $k/\theta$  in terms of  $\eta$ . An expression for  $k/\theta$  can be obtained by utilizing the relations presented in references (9) and (10) for  $\eta$  and  $\theta$ , and can be written as:

$$\frac{k}{\theta} = \left(1 + \frac{\gamma-1}{2} M_e^2\right) \frac{\int_0^{\eta_k} [1 + S - \sigma(u/u_e)^2] d\eta}{\int_0^\infty u/u_e (1 - u/u_e) d\eta} \quad (8)$$

By the use of equations (7) and (8), a value for the critical roughness Reynolds number based on flow properties evaluated just outside of the boundary layer can be determined. Hence, if the unit Reynolds number of the flow just outside of the boundary layer is known, a value for the critical roughness height required to produce premature boundary layer transition can be determined.

#### CALCULATIONS AND PRESENTATION OF RESULTS

The velocity and enthalpy profiles presented in reference (9) allows a value for  $k/\theta$  to be calculated for any specified values of  $\eta_k$  and Mach number from equation (8). This value of  $k/\theta$  can be substituted into equation (7) along with the appropriate values of  $u_k/u_e$  and  $S_k$  that correspond to

that value of  $\eta_k$  that has been specified. Further, substitution of values for  $M_e$  and  $T_e$  allows a value for  $Re_\theta/R_{kk}$  to be calculated.

The velocity and temperature profiles given in reference (9) are identified by a wall enthalpy function,  $S_w$ , and a pressure gradient parameter  $\beta$ . The wall enthalpy function is defined as:

$$S_w = \frac{T_w}{T_o} - 1 \quad (9)$$

A method for obtaining a value for  $\beta$  will be discussed under the section entitled "General Application of Method." Velocity and temperature profiles are presented in reference (9) for five values of  $S_w$  in the range  $-1 \leq S_w \leq 1$ . The  $S_w = -1$  corresponds to a wall temperature of absolute zero while the  $S_w = 1$  corresponds to a wall temperature twice the free stream stagnation temperature. For each of five values of  $S_w$ , the velocity and enthalpy profiles are presented for a range of values of  $\beta$  from 2 to less than -0.1. The  $\beta = 2$  represents an infinitely favorable pressure gradient, while  $\beta < 0$  represents adverse pressure gradients.

A value for  $Re_k/R_{kk}$  is obtained from the following equation using the calculated value for the ratio  $Re_\theta/R_{kk}$ .

$$\frac{Re_k}{R_{kk}} = \frac{Re_\theta}{R_{kk}} \cdot \frac{k}{\theta} \quad (10)$$

This procedure for calculating values of  $Re_k/R_{kk}$  was carried out using a high-speed digital computer. Velocity and enthalpy profiles presented in reference (9) for all five values of  $S_w$  were used. For each value of  $S_w$ , profiles for a large range of values of  $\beta$  representing both favorable and adverse pressure gradients were utilized. Values of  $\eta_k$  were chosen from 0.1 to the value corresponding to the outer edge of the boundary layer for increments of  $\eta_k = 0.1$ . These calculations were carried out for Mach numbers from 0 to 5 in increments of 1 Mach number. Because Sutherland's formula was used to represent the viscosity temperature relationship, it can be seen from equation (7) that  $Re_\theta/R_{kk}$  is dependent also upon  $Te$ . It will be shown later, however, that  $Re_\theta/R_{kk}$  and hence  $Re_k/R_{kk}$  is insensitive

to variations of  $Te$  so that all of the calculations to be presented were performed for a constant value of  $Te = 500^\circ R$ .

The results of these calculations are presented in graphical form as a family of curves of constant Mach number plotted as  $Re_{\theta}/R_{kk}$  versus  $Re_k/R_{kk}$ . A separate

chart is presented for each combination of values of  $S_w$  and  $\beta$  used in the calculations. These charts are presented as Figures 1. The upper limit on the values of  $Re_{\theta}/R_{kk}$  presented in these figures was dictated by the choice of  $\eta_k = 0.1$  as the minimum value of  $\eta_k$  for which the calculations were performed. Since the correlation between the roughness height required to produce premature transition and a critical roughness Reynolds number is valid only for roughness elements within the boundary layer, the calculations were performed only for values of  $\eta$  equal to or less than that value which corresponds to the boundary layer thickness. This fact dictates the lower limit on the values of  $Re_{\theta}/R_{kk}$ .

To illustrate the insensitiveness of  $Re_k/R_{kk}$  to variations of  $Te$ , calculations of the type previously indicated have been performed letting  $Te$  vary from  $100^{\circ}R$  to  $1,000^{\circ}R$ . The calculations were performed for  $S_w = 0$ , and  $\beta = 0$ . The results of the calculations are presented in Figure 2 as a plot of  $Re_k/R_{kk}$  versus  $Te$  with a family of curves of constant values of  $Re_{\theta}/R_{kk}$ . These curves are for a Mach number of 5.

Although curves have been presented for Mach numbers from 0 to 5 sufficient data are not currently available to indicate positively that the correlation between roughness height and critical roughness Reynolds number remains valid at hypersonic Mach numbers.

It is known, however, that as the Mach number increases, the distance between the roughness elements and the point of transition increases where the height of the roughness elements used is equal to the critical height. This was pointed out, for instance, by Van Driest and Blumer (reference (6)). Therefore, at hypersonic Mach numbers, it may become difficult to produce transition in the near vicinity of the roughness elements. Even though premature transition can be produced by the application of roughness elements, it usually occurs far downstream of the location of the roughness.



## GENERAL APPLICATION OF METHOD

To apply the results of the method presented, it is necessary to specify values for  $S_w$  and  $\beta$ , the enthalpy and pressure gradient parameters, that correspond to the point at which the roughness elements are to be located. The value for  $S_w$  can be determined from equation (9). In order to determine the value of  $\beta$ , it is more convenient to relate it to the correlation number  $n$  defined in reference (10). The relation between  $\beta$  and  $n$  is given graphically in Figure 3 as a plot of  $\beta$  versus  $n$ . Five curves, one for each of the five values of  $S_w$  are presented. The value of  $n$  corresponding to the point of interest can be calculated from the relation given in reference (10) as:

$$n = -\frac{\theta^2}{V_w} \left( \frac{T_w}{T_e} \right)^2 \frac{T_o}{T_e} \frac{du_e}{dx} \quad (11)$$

This expression can be written in a more convenient form for the purpose of this report as:

$$n = -R_{e\theta} \frac{\theta}{M_e} \frac{T_w}{T_e} \frac{\mu_e}{\mu_w} \frac{dM_e}{dx} \quad (12)$$

Values for  $S_w$  and  $\beta$  are now available which will allow the correct chart of  $Re_k/R_{kk}$  versus  $Re_\theta/R_{kk}$  to be found. The relation between  $Re_k/R_{kk}$  and  $Re_\theta/R_{kk}$  is specified by knowing the local Mach number which identifies the correct curve on the chart.

At this point it is necessary to choose the value for the critical roughness Reynolds number,  $R_{kk}$ . A review of the experimental investigations reported in references (4), (5), (6), and (7), indicates that a reasonable value for the critical roughness Reynolds number required to initiate premature transition is approximately 700 if three-dimensional roughness elements are used. To move transition to the location of the roughness, a value slightly larger than 700 should be used for the lower supersonic Mach numbers. As was previously mentioned in the section entitled "Calculations and Presentation of Results,"

it may be difficult at the higher supersonic Mach numbers to shift transition to the roughness location. It is a direct process utilizing the proper chart in Figures 1 to obtain a value for  $Re_k$  once an appropriate value for  $R_{kk}$  has been

chosen. Finally, a value for the roughness height is obtained by dividing the value of  $Re_k$  by the local unit Reynolds number.

The application of this method to a specific case will rarely involve values of  $S_w$ ,  $\beta$ , and  $Me$  which correspond exactly to any of the values of these quantities presented in Figures 1. It will therefore be necessary to interpolate using the information in Figures 1 to obtain a value for the roughness height which applies to the specific case. For the local Mach number,  $Me$ , a graphic interpolation can be performed, while for the quantities  $S_w$  and  $\beta$ , numerical interpolation is required. From Figure 4, which is a typical plot of  $Re_k/R_{kk}$  versus  $S_w$ , it can be seen that

a linear interpolation should be sufficiently accurate to determine  $Re_k/R_{kk}$  between any two adjacent values of  $S_w$  presented in Figures 1. Figure 4 has been presented for a constant local Mach number of 4 and  $Re_\theta/R_{kk}$  of 1. Figure 5

is the same type of plot as Figure 4 with the abscissa changed from  $S_w$  to  $\beta$  and the curves being a family of constant values of  $S_w$ . Again it can be seen from this figure that linear interpolation is sufficient except perhaps in certain regions of adverse pressure gradients. Figure 6 shows the variation of  $Re_k/R_{kk}$  with local Mach

number. These curves are presented as a family for constant values of  $S_w$ . All of the curves in Figure 6 are for  $\beta = 0$  (zero pressure gradient). Since curves are presented in Figures 1 for every Mach number between 0 and 5, it can be seen from Figure 6 that a linear interpolation should be sufficiently accurate to determine values for  $Re_k/R_{kk}$  at Mach numbers not specified.

Since the width of the roughness band in the stream-wise direction does not appear to be a critical parameter, it is suggested that for convenience a narrow band of roughness be used.

## APPLICATION OF METHOD OF A CONE

Since a sharp-nosed cone is quite often of interest to investigators, it was deemed worthwhile mentioning the application of the present method to this specific body shape. The value of  $S_w$  can be computed from equation (9) and since a cone is a zero pressure gradient body the value for  $\beta$  will be zero. The remaining information needed to enable the determination of the required roughness height to produce premature transition is a value for the local flow properties on the cone just outside of the boundary layer, and the boundary layer momentum thickness,  $\theta$ . The local flow properties can be obtained from any one of numerous references such as reference (11). The boundary layer momentum thickness for a cone is given in terms of the momentum thickness on a flat plate obtained at the same local Mach number, local Reynolds numbers, and wall to local temperature ratio by the following simple relations:

$$\theta_{\text{cone}} = \frac{1}{\sqrt{3}} \theta_{\text{flat plate}} \quad (13)$$

This equation can be readily developed by applying Mangler's transformation to flow over a flat plate. The flat plate momentum thickness is given by:

$$\theta_{\text{flat plate}} = \frac{C_F x}{2} \quad (14)$$

which is obtained by integrating the momentum equation. In equation (14)  $C_F$  is the mean skin friction coefficient, and  $x$  is the distance measured along the plate from the leading edge to this point of interest. The information in Figures 1 can be used to determine a value for the necessary roughness height after a value of  $\theta$  and hence  $Re_\theta$  for the cone has been determined.

CONCLUSION

A method has been presented for determination of the minimum height of surface roughness that causes premature laminar boundary layer transition. The method is based on the assumption that the height of the roughness necessary to accomplish this can be expressed as a critical roughness Reynolds number. The magnitude of the critical roughness Reynolds number has been determined experimentally by several different investigators and is quite consistent for the lower supersonic Mach numbers. Only a small amount of data is available for higher supersonic Mach numbers, and whether the critical roughness Reynolds number as a transition criterion holds, and if so, what its value is in the higher speed range, can only be determined by further experimentation. Since the charts which are presented in this report are independent of the value of the critical roughness Reynolds number, they may be used for any value of it.

REFERENCES

- (1) Von Doenhoff, A. E. and Horton, E. A., "A Low Speed Experimental Investigation of the Effect of a Sand-paper Type of Roughness on Boundary-Layer Transition," NACA Report 1349, 1958
- (2) Smith, A. M. O. and Clutter, D. W., "The Smallest Height of Roughness Capable of Affecting Boundary-Layer Transition in Low-Speed Flow," Douglas Aircraft Company Report No. ES26803, 1957
- (3) Smith, A. M. O. and Clutter, D. W., "The Smallest Height of Roughness Capable of Affecting Boundary-Layer Transition," Journal of the Aerospace Sciences, Vol. 26, No. 4, 1959
- (4) Clutter, D. W. and Smith, A. M. O., "Analysis of Further Data on the Effect of Isolated Roughness on Boundary-Layer Transition in Supersonic Flow," Journal of the Aerospace Sciences, Vol. 27, No. 1, 1960
- (5) Potter, J. L. and Whitfield, J. D., "Effects of Unit Reynolds Number, Nose Bluntness, and Roughness on Boundary Layer Transition," AEDC-TR-60-5, 1960
- (6) Van Driest, E. R. and Blumer, C. B., "Boundary Layer Transition at Supersonic Speeds - Three Dimensional Roughness Effects (Spheres)," North American Aviation, Inc. Report No. SID 61-275, 1961
- (7) Braslow, A. L., Knox, E. C., and Horton, E. A., "Effect of Distributed Three-Dimensional Roughness and Surface Cooling on Boundary Layer Transition and Lateral Spread of Turbulence at Supersonic Speeds," NASA TN D-53, 1959
- (8) Jackson, M. W. and Czarnecki, K. R., "Investigation by Schlieren Techniques of Methods of Fixing Fully Turbulent Flow on Models at Supersonic Speeds," NASA TN-D-242, 1960
- (9) Cohen, C. B. and Reshotko, E., "Similar Solutions for the Compressible Laminar Boundary Layer with Heat Transfer and Pressure Gradient," NACA Report 1293, 1956

REFERENCES (Cont'd.)

- (10) Cohen, C. B. and Reshotko, E., "The Compressible Laminar Boundary Layer with Heat Transfer and Arbitrary Pressure Gradient," NACA Report 1294, 1956
- (11) Staff of the Computing Section, Center of Analysis (under direction of Zdenek Kopal), "Tables of Supersonic Flow Around Cones," Technical Report No. 1, Massachusetts Institute of Technology, 1947




FIG. 1 VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER

$S_w = 1.0, \beta = 2.0$




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER






FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER





FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER



$S_w = 1.0, \beta = 0.3$

FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER





FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER



$S_w=1.0, \beta=-0.1305$

FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER






FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER  
 $S_w^* = 0.4, \beta = -0.2$






FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER





FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER



$S_w = -0.8, \beta = -0.14$

FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER





FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER



$S_w = 0.8, \beta = -0.325$

FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER






FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER  
 $S_w^+ = 1.0, \beta = 0$






FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER




$S_w = -1.0, \beta = -0.3$

FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER



$S_w = -1.0, \beta = -0.36$

FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER



$S_w = -1.0, \beta = -0.3884$

FIG. 1 (CONT.) VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH MOMENTUM THICKNESS REYNOLDS NUMBER






FIG. 2 VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH LOCAL TEMPERATURE




FIG.3 VARIATION OF PRESSURE GRADIENT PARAMETER  $\beta$   
WITH THE CORRELATION NUMBER  $n$




FIG. 4 VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH  $S_w$




FIG. 5 VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH  $\beta$




FIG. 6 VARIATION OF ROUGHNESS REYNOLDS NUMBER WITH  $M_0$

## External Distribution List

	<u>No. of Copies</u>
Chief, Bureau of Naval Weapons	
Department of the Navy	
Washington 25, D. C.	
Attn: RMMO	1
Attn: RMGA	1
Attn: RRMA	1
Attn: RRRE	1
Director, Special Projects	
Department of the Navy	
Washington 25, D. C.	
Attn: SP-20	1
Attn: SP-27	1
Attn: SP-272	1
Office of Naval Research	
Room 2709-T-3	
Washington 25, D. C.	
Attn: Head, Mechanics Branch	1
Commanding Officer	
Office of Naval Research	
Branch Office, Box 39, Navy 100	
Fleet Post Office, New York, N. Y.	5
Director, DTMB	
Aerodynamics Laboratory	
Washington 7, D. C.	
Attn: Library	1
Commander	
U. S. Naval Ordnance Test Station	
China Lake, California	
Attn: Technical Library	1
Director	
Naval Research Laboratory	
Washington 25, D. C.	
Attn: Library	1
Naval Weapons Laboratory	
Dahlgren, Virginia	
Attn: Library	1

NOLTR 61-87

External Distribution List

	<u>No. of Copies</u>
NASA Ames Research Center Moffett Field, California Attn: Librarian	1
NASA Langley Research Center Langley Field, Virginia Attn: Librarian	1
NASA Lewis Research Center 21000 Brookpart Road Cleveland, Ohio Attn: Mr. George Mandel, Chief, Library	1
Office of the Assistant Secretary of Defense (R&D) Room 3E1041, The Pentagon Washington 25, D. C. Attn: Technical Library	1
Research and Development Board Room 3D1041, The Pentagon Washington 25, D. C. Attn: Library	1
ASTIA Arlington Hall Station Arlington 12, Virginia Attn: TIPDR	10
Commander, NMC Point Mugu, California Attn: Technical Library	1
Commanding General Aberdeen Proving Ground, Md. Attn: Technical Information Branch	1
Attn: Ballistics Research Laboratories	1
Chief, DASA The Pentagon Washington, D. C. Attn: Document Library	1

NOLTR 61-87

External Distribution List

	<u>No. of Copies</u>
Commander Wright Air Development Division Wright-Patterson Air Force Base, Ohio	
Attn: WCOSI-3	1
Attn: WCLSW-5	1
Attn: WCRRD	1
Commander, AFBSD Air Research & Development Command P. O. Box 262 Inglewood, California	
Attn: WDTLAR	1
Attn: WDTVR	1
Commanding Officer, DOFL Washington 25, D. C.	
Attn: Library Rm. 211, Bldg. 92	1
NASA George C. Marshall Space Flight Center Huntsville, Alabama	
Attn: M-S&M-PT (Mr. H. A. Connell)	1
Attn: Dr. W. R. Lucas (M-SFM-M)	1
Attn: Dr. Ernst Geissler	1
Aerospace Corporation El Segundo, California	
Attn: Dr. Bitondo	1
APL/JHU 8621 Georgia Avenue Silver Spring, Maryland	
Attn: Tech. Reports Group	2
Attn: Librarian	1
(Via: BUWEPSREP)	
AVCO Manufacturing Corporation Research & Advanced Development Division 201 Lowell Street Wilmington, Massachusetts	
Attn: Mr. I. Sacks	1

NOLTR 61-87

External Distribution List

	<u>No. of Copies</u>
AVCO Research Laboratory 2385 Revere Beach Parkway Everett 49, Massachusetts Attn: Technical Library	1
General Electric Company Space Vehicle & Missiles Department 21 South 12th Street Philadelphia, Pennsylvania Attn: Mr. J. Heiser	1
General Electric, Research Laboratory 3198 Chestnut Street Philadelphia, Pennsylvania Attn: Dr. Leo Steg Attn: Mr. J. Persh	1 1
NASA 1520 H Street, N. W. Washington, D. C.	5
NASA High Speed Flight Station Edwards Field, California Attn: W. C. Williams	1
Polytechnic Institute of Brooklyn 527 Atlantic Avenue Freeport, New York Attn: Dr. Paul A. Libby (Via: Commanding Officer Office of Naval Research Branch Office 346 Broadway New York 13, New York)	1
General Applied Sciences Laboratories, Inc. Merrick and Stewart Avenues East Meadow, New York Attn: Mr. R. Byrne	1
National Bureau of Standards Washington 25, D. C. Attn: Dr. Galen B. Schubauer	1



External Distribution List

	<u>No. of Copies</u>
Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena 3, California Attn: I. R. Kowlan, Chief, Reports Group	1
Institute for Defense Analyses Advanced Research Projects Agency Washington 25, D. C. Attn: Mr. W. G. May General Sciences Branch	1
United Aircraft Corporation Research Laboratories East Hartford 8, Connecticut Attn: Mr. H. J. Charette Attn: Mr. H. Taylor	1 1
Commanding General Army Rocket and Guided Missile Agency Redstone Arsenal, Alabama Attn: Mr. John Morrow	1
Cornell Aeronautical Laboratory 4455 Genesee Street Buffalo, New York Attn: Dr. Gordon Hall	1
The Catholic University of America Washington, D. C. Attn: Dr. K. F. Herzfeld Attn: Dr. Max Munk	1 1
AF Office of Scientific Research Washington, D. C. Attn: Librarian	1
Lehigh University Physics Department Bethlehem, Pennsylvania Attn: Dr. R. Emrich	1

External Distribution List

	<u>No. of Copies</u>
University of Michigan Ann Arbor, Michigan Attn: Dr. Arnold Kuethe	1
National Science Foundation Washington 25, D. C. Attn: Dr. R. Seeger	1
Supervisor Technical Documents Services Willow Run Laboratories University of Michigan Willow Run Airport Ypsilanti, Michigan	1
Ohio State University Research Foundation Columbus 10, Ohio Attn: Security Officer	1
Case Institute of Technology Cleveland 6, Ohio Attn: G. Kuerti	1
AEDC VKF Arnold Air Force Station, Tennessee Attn: Mr. Potter Attn: Technical Library	1 1
Brown University Providence 12, Rhode Island Attn: Library	1
University of California Institute of Engineering Research Berkeley 4, California	1
California Institute of Technology Guggenheim Aeronautical Laboratory Pasadena 4, California Attn: Aeronautics Library	1
Cornell University Graduate School of Aeronautical Engineering Ithaca, New York	1

## External Distribution List

	<u>No. of Copies</u>
The Johns Hopkins University Baltimore 18, Maryland Attn: Prof. F. Clauser	1
University of Maryland College Park, Maryland Attn: Prof. W. Sherwood	1
Attn: Dr. S. I. Pai	1
Attn: Dr. F. R. Hama	1
Attn: Dr. R. Weske	1
Attn: Prof. Shreve	1
Massachusetts Institute of Technology Cambridge 39, Massachusetts Attn: Aeronautics Library	1
Massachusetts Institute of Technology Lincoln Laboratory Lexington, Massachusetts	1
Rosemount Aeronautical Laboratories University of Minnesota Minneapolis, Minnesota	1
The James Forrestal Research Center Princeton University Princeton, New Jersey Attn: Library	1
Princeton University Dept. of Aeronautical Engineering Princeton, New Jersey	1
University of Southern California Engineering Center Library 3518 University Avenue Los Angeles 7, California	1
Stanford University Dept. of Aeronautical Engineering Stanford, California	1
Defense Research Laboratory University of Texas P. O. Box 8029 Austin 12, Texas Attn: Dr. Thompson	1

NOLTR 61-87

External Distribution List

	<u>No. of Copies</u>
Yale University Dept. of Mechanical Engineering New Haven 10, Connecticut Attn: Dr. P. Wegener	1
Boeing Scientific Research Laboratories P. O. Box 3981 Seattle 24, Washington Attn: Research Library	1
Douglas Aircraft Company Missile and Space Systems Division 3000 Ocean Park Boulevard Santa Monica, California Attn: Library	1
Douglas Aircraft Company 827 Lapham Street El Segundo, California Attn: Library	1
Hughes Aircraft Company Research and Development Laboratories Culver City, California Attn: Library	1
Lockheed Missiles and Space Company Sunnyvale, California Attn: Library	1
Lockheed California Company 2406 N. Hollywood Way Burbank, California Attn: Library	1
Lockheed Georgia Company Marietta, Georgia Attn: Library	1
McDonnell Aircraft Corporation P. O. Box 516 St. Louis 66, Missouri Attn: Library	1

## External Distribution List

	<u>No. of Copies</u>
North American Aviation, Inc. Space Sciences Laboratory 12214 Lakewood Boulevard Downey, California	1
The Martin Company Baltimore 3, Maryland Attn: Library	1
Northrop Aircraft, Inc. Hawthorne, California Attn: Library	1
Republic Aviation Corporation Farmingdale, Long Island, New York Attn: Library	1
Space Technology Laboratories, Inc. Redondo Beach, California Attn: Library	1
Convair Fort Worth Division Fort Worth 1, Texas Attn: Library	1
Convair Scientific Research Laboratory P. O. Box 950 San Diego 12, California Attn: Library	1
Aerospace Corporation El Segundo, California Attn: Library	1
Chance - Vought Aircraft, Inc. High Speed Wind Tunnel Section Dallas, Texas Attn: Mr. J. Cooksey	1
Ling - Tempco - Vought Research Center Dallas, Texas Attn: Dr. F. Fenter	1

# CATALOGING INFORMATION FOR LIBRARY USE

BIBLIOGRAPHIC INFORMATION					
	DESCRIPTORS	CODES	SECURITY CLASSIFICATION AND CODE COUNT	DESCRIPTORS	CODES
SOURCE	NOL technical report	NOLTR		Unclassified - 14	U014
REPORT NUMBER	61-87	610087	CIRCULATION LIMITATION		
REPORT DATE	Oct. 1962	1062	CIRCULATION LIMITATION OR BIBLIOGRAPHIC		
			BIBLIOGRAPHIC (SUPPL., VOL., ETC.)		

SUBJECT ANALYSIS OF REPORT					
	DESCRIPTORS	CODES	DESCRIPTORS	CODES	CODES
Aerodynamic	AERD		Velocity	VELC	
Boundary layer	BOUL		Enthalpy	ENTH	
Turbulent	TUBU				
Flow	FLOW				
Roughness	ROUG				
Transition	TRNI				
Reynolds number	REYN				
Flow (Properties)	FLOWP				
Experimental	EXPE				
Parameters	PARA				
Subsonic	SUBS				
Supersonic	SUPR				

<p>Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 61-87) THE DETERMINATION OF CRITICAL ROUGHNESS HEIGHT FOR BOUNDARY LAYER TRANSITION, by W. C. Lyons, Jr. and Z. J. Levensteins. 25 Oct. 1962. 12p. charts, tables (Ballistics research report 49). NOL task 363.</p> <p>UNCLASSIFIED</p> <p>A method is presented which allows a determination of the critical roughness height required to produce premature boundary layer transition. This method is applicable to cases involving compressibility, heat transfer, and pressure gradient. The results are presented in graphic form which allows a relatively simple application of the method.</p>	<p>1. Boundary layer - Transition</p> <p>2. Boundary layer, Turbulent</p> <p>I. Lyons, W. Carson</p> <p>II. Levensteins, Zigurds J., jt. author</p> <p>III. Series</p> <p>IV. Project</p>	<p>Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 61-87) THE DETERMINATION OF CRITICAL ROUGHNESS HEIGHT FOR BOUNDARY LAYER TRANSITION, by W. C. Lyons, Jr. and Z. J. Levensteins. 25 Oct. 1962. 12p. charts, tables (Ballistics research report 49). NOL task 363.</p> <p>UNCLASSIFIED</p> <p>A method is presented which allows a determination of the critical roughness height required to produce premature boundary layer transition. This method is applicable to cases involving compressibility, heat transfer, and pressure gradient. The results are presented in graphic form which allows a relatively simple application of the method.</p>	<p>1. Boundary layer - Transition</p> <p>2. Boundary layer, Turbulent</p> <p>I. Lyons, W. Carson</p> <p>II. Levensteins, Zigurds J., jt. author</p> <p>III. Series</p> <p>IV. Project</p>
<p>Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 61-87) THE DETERMINATION OF CRITICAL ROUGHNESS HEIGHT FOR BOUNDARY LAYER TRANSITION, by W. C. Lyons, Jr. and Z. J. Levensteins. 25 Oct. 1962. 12p. charts, tables (Ballistics research report 49). NOL task 363.</p> <p>UNCLASSIFIED</p> <p>A method is presented which allows a determination of the critical roughness height required to produce premature boundary layer transition. This method is applicable to cases involving compressibility, heat transfer, and pressure gradient. The results are presented in graphic form which allows a relatively simple application of the method.</p>	<p>1. Boundary layer - Transition</p> <p>2. Boundary layer, Turbulent</p> <p>I. Lyons, W. Carson</p> <p>II. Levensteins, Zigurds J., jt. author</p> <p>III. Series</p> <p>IV. Project</p>	<p>Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 61-87) THE DETERMINATION OF CRITICAL ROUGHNESS HEIGHT FOR BOUNDARY LAYER TRANSITION, by W. C. Lyons, Jr. and Z. J. Levensteins. 25 Oct. 1962. 12p. charts, tables (Ballistics research report 49). NOL task 363.</p> <p>UNCLASSIFIED</p> <p>A method is presented which allows a determination of the critical roughness height required to produce premature boundary layer transition. This method is applicable to cases involving compressibility, heat transfer, and pressure gradient. The results are presented in graphic form which allows a relatively simple application of the method.</p>	<p>1. Boundary layer - Transition</p> <p>2. Boundary layer, Turbulent</p> <p>I. Lyons, W. Carson</p> <p>II. Levensteins, Zigurds J., jt. author</p> <p>III. Series</p> <p>IV. Project</p>